

# KD-HDDA1X8

1 Input to 8 Outputs HDMI Distribution Amplifier

## Advanced HDMI® Features

- » **3D** – Capability to pass 3D stereoscopic signal formats



## Specifications



### Technical:

---

- » **Inputs:** 1 HDMI connector
- » **Outputs:** 8 HDMI connectors
- » **Bandwidth:** 3.4 Gb/s TMDS bandwidth
- » **Link:** Single Link: 1080p/60, 12 bit color depth, 1920x1200 max.
- » **DDC Signal (Data):** Input DDC Signal: 5 Volts p-p (TTL)
- » **HDMI® and HDCP Licensing:** Fully licensed and compatible with all HDMI and HDCP technologies
- » **HDMI Video/Audio Signal:** Input Video Signal: 1.2 Volts p-p
- » **HDMI Connector:** Type A, 19 Pin Female
- » **DDC Communication:** EDID and HDCP Bi-directional Transparency from Display to Source
- » **EDID Control:** Any of the active outputs connected via HDMI, or from an internal library of 6 default EDID settings.
- » **Power Source:** 5 Volt DC @ 3 Amps, 100-240 VAC, 50-60 Hz

### General

---

- » **Regulation:** CE, RoHS, WEEE
- » **Rack Mount:** 1U Rack Ears Included
- » **Accessories:** Rack Ears, KD-PS5V3A UL Certified Power Supply +5V, 3A
- » **Product Dimensions:** 17" x 4" x 1.75"
- » **Shipping Carton Size:** 18.75" x 9.5" x 3.5"
- » **Product Weight:** 3.2 lbs
- » **Shipping Weight:** 5 lbs
- » **Enclosure:**